

INTERLINKED SMOKE ALARM

Not Just An Early Warning. It Could Be Your Only Warning.



Product Overview

Our interconnect smoke alarm is equipped with photoelectric sensor which is highly effective in detecting smoldering fires (common traits of residential fires).

Its interconnect feature allows up to 30 units to be paired, including heat alarms (purchased separately). This provides a robust, wide smoke detection coverage for any type of residential properties. Once smoke is detected, all paired alarms will sound off to inform her occupants.

Its hush/test button is big & easy to reach with a pole, making hushing and testing a breeze. You can also link to a remote control (purchased separately) for easy testing and silencing.

Key Features

- ✓ Photoelectric Sensor
- ✓ TUV Certified
- ✓ SCDF Approved
- ✓ Up To 30 Units Per Cluster
- ✓ Long Trans Distance
- ✓ 10 Years Lithium Battery
- ✓ No Drilling Required
- ✓ Easy To Reach Test Button
- ✓ Linkable To Remote Control & Heat Alarm (FSI3002)



Technical Specifications (SD01)

Sensor Type	Photoelectric	Alarm Sound	>85dB/3M
Power Supply	Lithium (non replaceable)	Humidity	15% - 95%RH (No Condensation)
Wireless Frequency	433.92MHz	Temperature	-10°C ~ +55°C
Wireless Distance	100M (open area)	Material	ABS Fire Retardant
Max Wireless Connect	30 units	Standard	EN14604:2005/AC:2008
Dimensions	130mm Diameter x 25mm Height	Weight	129gm



Whatsapp for pricing

88158752